



# F110-EX FULLY RUGGED TABLET

- ATEX & IECEx Explosive Atmosphere Certified
- Enhanced Enterprise Security with TPM 2.0, optional Intel vPro and Windows Hello face-authentication camera
- 8th Generation Intel® Core™ i7 / i5 Processor
- 11.6" LumiBond® 2.0 Display with Getac Sunlight Readable Technology and Capacitive Touchscreen
- Optional 1D / 2D Imager Barcode Reader and LF / HF RFID Reader



# Specifications

## Operating System

Windows 10 Pro

## Mobile Computing Platform

Intel® Core™ i5-8265U Processor 1.6GHz  
Max. 3.9GHz with Intel® Turbo Boost Technology  
- 6MB Intel® Smart Cache

## Platform Options:

Intel® Core™ i5-8365U vPro™ Processor 1.6GHz  
Max. 4.1GHz with Intel® Turbo Boost Technology  
- 6MB Intel® Smart Cache

Intel® Core™ i7-8565U Processor 1.8GHz  
Max. 4.6GHz with Intel® Turbo Boost Technology  
- 8MB Intel® Smart Cache

Intel® Core™ i7-8665U vPro™ Processor 1.9GHz  
Max. 4.8GHz with Intel® Turbo Boost Technology  
- 8MB Intel® Smart Cache

## VGA Controller

Intel® UHD Graphics

## Display

11.6" IPS TFT LCD FHD (1920 x 1080)

Protection film

800 nits LumiBond® display with Getac sunlight readable technology  
Capacitive multi-touch screen

## Storage & Memory

8GB DDR4

Optional: 16GB / 32GB DDR4

256GB SATA SSD

Optional: 512GB / 1TB SATA SSD

Optional: 256GB / 512GB / 1TB PCIe NVMe SSD

## Keyboard

Power button

5 tablet programmable buttons

## Pointing Device

Touchscreen

- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

## Expansion Slot

Optional: 1D / 2D imager barcode reader

## I/O Interface

FHD webcam x 1 <sup>vi</sup>

8M pixels auto focus rear camera x 1

Headphone out / mic-in combo x 1

DC in Jack x 1

USB 3.2 Gen 2 Type-A x 1

HDMI x 1

Optional: Windows Hello face-authentication camera (front-facing) x 1 <sup>vii</sup>

## Communication Interface

Intel® Dual Band Wireless-AC 9260, 802.11ac

Bluetooth (v5.1) <sup>i</sup>

Optional: Dedicated GPS

Optional: 4G LTE mobile broadband

## Security Feature

TPM 2.0

Kensington Lock

Optional: Intel® vPro™ Technology

Optional: LF / HF RFID reader <sup>ii,iii</sup> or HF RFID reader <sup>iv</sup>

## Power

AC adapter (65W, 100-240VAC, 50 / 60Hz)

Li-Ion smart battery (11.4V, typical 2160mAh;

min. 2100mAh) x 2

## Dimension (W x D x H) & Weight

314 x 207 x 24.5 mm (12.4" x 8.15" x 0.96")

1.49 kg (3.28 lbs) <sup>v</sup>

## Rugged Feature

MIL-STD-810H certified

IP65 certified

Vibration & 4 feet (1.2m) drop resistant <sup>ix</sup>

ATEX & IECEx Certified

## Environmental Specification

Temperature <sup>ix</sup>:

- Operating: -21°C to 60°C / -6°F to 140°F

- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:

- 95% RH, non-condensing

## Explosion Protection

ATEX / IECEx Zone 2/22

Ex II 3G Ex ic op is IIC T4 Gc

Ex II 3D Ex ic op is IIIB T130°C Dc

## Pre-installed Software

Getac Utility

Getac Camera

Getac Geolocation

Getac Barcode Manager <sup>viii</sup>

Optional: Absolute Persistence®

## Accessories

Battery (11.4V, typical 2160mAh; min. 2100mAh)

AC Adapter (65W, 100-240VAC)

Capacitive Stylus

## Optional:

Battery (11.4V, typical 2160mAh; min. 2100mAh)

AC Adapter (65W, 100-240VAC)

Hand Strap

Digitizer Pen

Capacitive Stylus

Protection Film

Shoulder Strap (2-point)

Shoulder Harness (4-point; handsfree)

## Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

## Standard

3 years Bumper-to-Bumper

- Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- LF (125kHz) / HF(13.56MHz) Combo RFID / NFC reader (iClass, HID Prox, ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- LF/HF RFID reader option is not Energy Star 8.0 compliant.
- 13.56MHz Contactless HF RFID reader (ISO 15693, 14443 A / B, Mifare and FeliCa™ compliant).
- Weight and dimensions vary from configurations and optional accessories.
- Tested by an independent third-party test lab following MIL-STD-810H.
- FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- Available when barcode reader option is selected.
- Drop test results vary from configurations and optional accessories.

# F110-EX

## Fully Rugged Tablet



# Getac

## GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd.,  
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C

Tel : +886 2 2785 7888

globalmarketing@getac.com | www.getac.com



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.  
Information provided herewith is for reference only,  
available specification shall be subjected to quotation by request. V01M03Y21WWW